



DEPRO® - HCRM

High Current Relay Module



- **15A, 1 form C (SPDT) contact**
- **Compact, requires just 30mm of DIN rail**
- **Class 1 Division 2 / Zone 2 certified**

The DEPRO® - HCRM is designed to interface a PLC/DCS digital output to a high current load device. The coil is rated 24Vdc and the 1 form C contact is rated up to 12Vdc or 240Vac at 15A.

This relay has been approved for use in Class 1 Division 2 / Zone 2 hazardous locations.



SPECIFICATIONS

Catalog Number:	330218	
Input (coil):	24Vdc nominal 18-32Vdc 40mA @ 24Vdc	
Output (contacts):	12Vdc / 240Vac 15A max. 2HP, 240Vac 1 form C (SPDT)	
Contact material:	AgCdO	
Operating Time:	<15ms turn on <10ms turn off	
Terminations:	Coil 26-12AWG 0.5-0.6Nm torque 6mm stripping length	Contacts 26-10AWG 0.5-0.6Nm torque 7mm stripping length
Temperature:	-20° to +50°C ambient	
Mounting:	32mm and 35mm DIN rails	
Approvals:	cCSAus Class 1 Division 2 Groups A,B,C and D Temperature code T5 Zone 2, Ex nA IIC	

