



X2 base 7 v2 7" HMI with iX runtime

800 × 480 pixel (5:3)
TFT-LCD touch screen
1 × Ethernet, 4 × Serial, 1 × USB as standard
Operating temperature -10° to +50° C
CE, FCC, UL approvals

Facts

General description

Part number	630005210
Life cycle status	Active
Warranty	2 year

Certifications

General	CE, FCC, UL 61010-2-201
Safety	UL 61010-1, UL 61010-2-201, CAN/CSA-C22.2 No. 61010-1, CAN/CSA-C22.2 No. 61010-2-201

Mechanical

Mechanical size	202 x 152 x 37mm
	Panel Mount
	1million finger touch operations
Touch type	Resistive
Cut-out size	186 x 136mm
Weight	0.58 kg
Housing material	Plastic (PC+ABS), Gray
Buzzer	No
LED	No

Power

Input voltage	24 V DC (18 to 32 VDC) CE: The power supply has to be conform with the requirements according to IEC 60950 and IEC 61558-2-4.UL and cUL: The power supply has to be conform with the requirements for class II power supplies.
Power consumption (max)	5.6 W
Input fuse	Internal DC fuse

CPU	ARM Cortex A8 600MHz
RAM	512 MB
FLASH	2 GB

Display

Size diagonal	7.0" diagonal
Resolution	800 × 480 pixel (5:3)
Backlight	LED Backlight
Backlight life time	20000 hours
Backlight brightness	400 cd/m²
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

Drivers

Digital IO

Digital output	No
----------------	----

Serial communication

Number of serial ports	1port9pinDsub, 1port3pinScrew
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS 485
Serial port 6	RS 485

Ethernet communication

Number of Ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

Expansion interface

Expansion port	No
SD card	No
USB	1

Environmental

Operating temperature	-10°C to +50°C
Storage temperature	-20°C to +60°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65, NEMA 4X/ 12 and UL 50E Type 4X/ 12
Sealing back	IP20
Humidity	5% – 85% non-condensed

ABB - COMLI Master (5.7.2)
ABB - COMLI Slave (4.11.0)
ABB - TotalFlow (5.2.1)
Allen Bradley - ControlLogix Ethernet IP (4.24.1)
Allen Bradley - DF1 (5.8.0)
Allen Bradley - DH485 (4.6.2)
Allen Bradley - MicroLogix Ethernet (5.6.0)
Allen Bradley - SLC5/PLC5 Ethernet (5.4.0)
Altus - Alnet I (5.8.0)
Animatics - SmartMotor (5.2.1)
Beckhoff - ADS (5.12.1)
Beckhoff - ADS Symbolic (4.7.0)
Beijer Electronics - iX Demo (4.4.0)
Beijer Electronics - Macro driver (4.0.7)
Bernecker + Rainer - Mininet (5.6.0)
BoschRexroth - IndraDrive C (5.2.1)
CODESYS - ARTI v2.x, v3.x (4.8.0)
CODESYS - SoftControl Direct Access (4.4.0)
Cognex - InSight (5.2.2)
Control Techniques - Unidrive (5.3.1)
CTC - Serial Binary (5.4.2)
Delta - PLC Modbus ASCII (5.6.0)
Emerson - Modbus Master RTU/ASCII (5.4.0)
Eurotherm - Easy Serial 631 (5.1.1)
Fatek - Facon (5.10.0)
Galil - DMC (5.2.2)
GE Fanuc - Ethernet SRTP (5.5.0)
GE Fanuc - SNPX (5.6.1)
Gidding & Lewis - Motion control (5.4.0)
IAI - Xsel (5.4.1)
Idec - Computer Link (5.8.0)
Johnson Control - JCONTROL (5.2.1)
KEB - COMBIVERT (5.4.0)
Keyence - KV-series (5.6.0)
Koyo - DirectNET (5.5.0)
Koyo - K Sequence (5.3.1)

Lenze - LECOM A/B (5.6.0)
LS Industrial System - Glofa (5.3.0)
LS Industrial System - Master K (5.4.0)
Matsushita - MEWTOCOL-COM (5.9.2)
Mitsubishi Electric - Alpha2 (5.7.0)
Mitsubishi Electric - A-series (C24) (5.6.0)
Mitsubishi Electric - A-series (CPU) (5.10.0)
Mitsubishi Electric - A-series (E71) (5.4.0)
Mitsubishi Electric - Freqrol FR-A PLC (5.8.2)
Mitsubishi Electric - FX Series ADP/BD (5.10.0)
Mitsubishi Electric - FX Series ENET (5.4.1)
Mitsubishi Electric - FX Series Serial (5.16.0)
Mitsubishi Electric - MC Protocol (5.11.4)
Mitsubishi Electric - MR-J2/MR-J3-T MELSERVO (5.9.0)
Mitsubishi Electric - QnA/Qnn Serial (5.10.0)
Mitsubishi Electric - QnA/Qnn (C24) (5.5.0)
Mitsubishi Electric - Q-Series Ethernet (E71) (5.5.0)
Modicon - Modbus Master (5.19.4)
Modicon - Modbus Slave RTU/TCP (4.20.2)
NEMA0183 - NEMA 0183 (4.6.0)
Omron - Ethernet IP (4.3.3)
Omron - FINS (5.9.5)
Omron - Host Link (5.6.0)
Regin - EXoline (5.3.2)
SAIA - S-BUS Serial/Ethernet (5.7.0)
Schneider Electric - Modbus (5.3.0)
Schneider Electric - TSX Uni-Telway (4.5.3)
Siemens - S5 PG/AS511 (5.4.0)
Siemens - S7 200 PPI (5.8.5)
Siemens - S7 over TCP (S7-200/300/400/1200/1500) (4.18.0)
Siemens - MPI (HMI Adapter) (5.7.0)
WAGO - Modbus TCP (5.10.0)
Vigor - M/VB-Series (5.6.0)
Yamaha - VIP (5.2.1)
Yaskawa - Memobus Master (5.7.0)
Yokogawa - FA-M3 (5.6.0)